

IN THE CLAIMS

Upon entry of the present amendment, the status of the claims will be as is shown below. This listing of claims replaces all previous versions and listings of claims in the present application.

1. (Currently Amended) A diagnosis supporting device connected to an endoscope system that captures an image of a subject ~~faced to the~~ facing a tip of an endoscope to generate special observation image data for displaying a special observation image for diagnosis based on ~~various~~ image data transmitted from the endoscope system, said diagnosis supporting device comprising:

a light emitting section that alternately emits excitation light to excite living tissue and reference light to illuminate the subject, said light emitting section including a light source that varies intensity of the excitation light and reference light in response to voltage applied to said light source;

a probe that is inserted through a forceps channel to guide the excitation light and the reference light from a proximal end to a distal end;

an image data acquiring section that acquires fluorescent image data generated by the endoscope system when the light emitting section emits the excitation light and acquires reference image data generated by the endoscope system when the light emitting section emits the reference light;

an intensity measuring section that extracts the maximum brightness level from the brightness levels of all the pixels in the fluorescent image data and extracts the maximum brightness level from the brightness levels of all the pixels in the reference image data whenever the image ~~signal~~ data acquiring section acquires a set of the

reference image data and the fluorescent image data;

a calculating section that calculates a first intensity coefficient based on the maximum brightness level of the fluorescent image data according to a first operational expression and that calculates a second intensity coefficient corresponding to the maximum brightness level of the reference image data according to a second operational expression; and

a light controller that controls the intensity of the excitation light according to the first intensity coefficient and that controls the intensity of the reference light according to the second intensity coefficient, said light controller controlling the intensities of said excitation light and said reference light without a variable diaphragm and without a light stop by changing the voltage applied to said light source,

wherein said first and second operational expressions are determined such that the intensities of said excitation light and said reference light increase as the maximum brightness levels of said fluorescent image data and said reference image data decrease.

2. (Cancelled)

3. (Currently Amended) The diagnosis supporting device according to claim 1, further comprising:

an affected-area-information acquiring section that determines whether a difference between brightness level of a pixel in said reference image data and brightness level of a pixel in said fluorescent image data at the corresponding position

is larger than a predetermined threshold value ~~or not~~ for all of the pixels in said reference image data whenever said image-signal data acquiring section acquires a set of said reference image data and said fluorescent image data, and that acquires position information that specifies the positions of the pixels ~~whose~~ with differences ~~are~~ larger than said threshold value;

an image generating section that generates color image data for displaying a monochromatic image on a monitor based on said reference image data acquired by said image data acquiring section;

an image composing section that composes said color image data generated by said image generating section and said position information to convert the pixels on said color image data that are represented by said position information into specified pixels exhibiting a predetermined color; and

an output section that ~~output~~ outputs the composed color image data composed by said image composing section as special observation image data.

4. (Currently Amended) The diagnosis supporting device according to claim 3, wherein said ~~specific~~ specified pixels ~~exhibit~~ are red.

5. (Currently Amended) The diagnosis supporting device according to claim 1, wherein said probe consists of a number of bundled optical fibers ~~that are bundled up with one another~~.